

MADE IN ITALY

Rubber hose for air or for water (40°C max.)

Only on request, available polyurethane hose or stainproof hose or grease 400 BAR


Metal case available also in stainless steel

Max. pressure:

18 bar/250 Psi

Weight: 20 Kg.

ITEM	INLET Bsp	OUTLET Bsp	MEASURE	LENGTH
BX17V20M8-14	3/8 F	3/8 M	8 x14	20 m / 65 ft
BX17V20M10-17	3/8 F	3/8 M	10 x 17	20 m / 65 ft
BX17V15M13-20	1∕₂ M	1/2 M	13 x 20	15 m / 50 ft



The automatic hose reels of the range V are suitable for transferring fluids at several pressures and temperatures.

The hose reels rewind automatically the hose by a spring located in the drum. The hose can be stopped at the desired length. The hot galvanized steel structure is moulded and coated with electrostatic polyester powder resistant to UV rays. The parts in contact with the fluid are specially treated to improve resistance to corrosion. The special open construction allows an easy assembly and replacement of the hose and permits control of the rewinding. The hose-guide arms can be fixed in three different positions according to the hose reel installation.

The range is divided into several models depending on hose diameters and lenghts. At request, versions equipped with special hoses can be supplied.

OPTIONAL: lateral protective covers, flexible hose for the connection to the system, revolving stand, 4-rollers hose guide, additional bracket for a quick fixing of the hose reel.

