

## **FILTER - REDUCER + LUBRICATOR**



**MADE IN ITALY**

Exhaust system is semi automatic - manual.

Upon request for some models can be required automatic.

Standard filtration grade is 20 $\mu$ .

Upon request can be required 5 $\mu$  or 50 $\mu$ .

### **BX11FRL14P - Thread 1/4**

|                    |             |
|--------------------|-------------|
| Max inlet pressure | 15 bar      |
| Output pressure    | 0 - 12 bar  |
| Cup capacity       | 22 cc.      |
| Filtration degree  | 20 $\mu$    |
| Flow rate          | 1100 NI/min |

### **BX11FRL38P - Thread 3/8**

|                    |             |
|--------------------|-------------|
| Max inlet pressure | 15 bar      |
| Output pressure    | 0 - 12 bar  |
| Cup capacity       | 22 cc.      |
| Filtration degree  | 20 $\mu$    |
| Flow rate          | 1100 NI/min |

### **BX11FRL12P - Thread 1/2**

|                    |             |
|--------------------|-------------|
| Max inlet pressure | 15 bar      |
| Output pressure    | 0 - 12 bar  |
| Cup capacity       | 46 cc.      |
| Filtration degree  | 20 $\mu$    |
| Flow rate          | 2500 NI/min |

### **BX11FRL34P - Thread 3/4**

|                    |             |
|--------------------|-------------|
| Max inlet pressure | 15 bar      |
| Output pressure    | 0 - 12 bar  |
| Cup capacity       | 90 cc.      |
| Filtration degree  | 20 $\mu$    |
| Flow rate          | 4300 NI/min |

### **BX11FRL1P - Thread 1"**

|                    |             |
|--------------------|-------------|
| Max inlet pressure | 15 bar      |
| Output pressure    | 0 - 12 bar  |
| Cup capacity       | 90 cc.      |
| Filtration degree  | 20 $\mu$    |
| Flow rate          | 4300 NI/min |