

UNIT FILTER + REDUCER + LUBRICATOR

MADE IN ITALY



Exhaust system is semi automatic - manual.

Upon request for some models can be required automatic.

Standard filtration grade is 20 μ .

Upon request can be required 5 μ or 50 μ .

BX11GFRL14P - Thread 1/4

Max inlet pressure	15 bar
Output pressure	0 - 12 bar
Cup capacity	22 cc.
Filtration degree	20 μ
Flow rate	1000 NI/min

BX11GFRL38P - Thread 3/8

Max inlet pressure	15 bar
Output pressure	0 - 12 bar
Cup capacity	22 cc.
Filtration degree	20 μ
Flow rate	1000 NI/min

BX11GFRL12P- Thread 1/2

Max inlet pressure	15 bar
Output pressure	0 - 12 bar
Cup capacity	46 cc.
Filtration degree	20 μ
Flow rate	2400 NI/min

BX11GFRL34P- Thread 3/4

Max inlet pressure	15 bar
Output pressure	0 - 12 bar
Cup capacity	90 cc.
Filtration degree	20 μ
Flow rate	4250 NI/min

BX11GFRL1P- Thread 1"

Max inlet pressure	15 bar
Output pressure	0 - 12 bar
Cup capacity	90 cc.
Filtration degree	20 μ
Flow rate	4250 NI/min