

3 BELT DRIVEN TWO STAGES

3.1 5,5HP



ALUMINUM CYLINDER

TECHNICAL SPECIFICATIONS

MODEL	PUMP	TANK	HP	VOLT	AIR DISPLACEMENT (L/MIN)	BAR	RPM	SIZE	KG
BX59/200CT 5,5	BX59	200	5,5	380	606	11	1400	145 X 50 X 107	121
BX59/270CT 5,5	BX59	270	5,5	380	606	11	1400	155 X 57 X 120	139
BX59/500CT 5,5	BX59	500	5,5	380	606	11	1400	203 X 68 X 131	209
BX59/500CT 7,5	BX59	500	7,5	380	705	11	1500	203 X 68 X 131	215
BX59/500FT 5,5	BX59	500	5,5	380	606	11	1400	203 x 68 X 131	205
BX59/500FT 7,5	BX59	500	7,5	380	705	11	1500	203 x 68 X 131	211

CAST IRON CYLINDER

TECHNICAL SPECIFICATIONS

MODEL	PUMP	TANK	HP	VOLT	AIR DISPLACEMENT (L/MIN)	BAR	RPM	SIZE	KG
BX59G/200CT 5,5	BX59G	200	5,5	380	606	11	1400	145 X 50 X 107	126
BX59G/270CT 5,5	BX59G	270	5,5	380	606	11	1400	155 X 57 X 120	144
BX59G/500CT 5,5	BX59G	500	5,5	380	606	11	1400	203 X 68 X 131	214
BX59G/500CT 7,5	BX59G	500	7,5	380	705	11	1500	203 X 68 X 131	220
BX59G/500FT 5,5	BX59G	500	5,5	380	606	11	1400	203 X 68 X 131	210
BX59G/500FT 7,5	BX59G	500	7,5	380	705	11	1500	203 X 68 X 131	216