

## 4 TANDEM

### 4.1 3HP - 4HP - 5,5HP - 7,5HP - 10HP - 15HP



#### ALUMINUM CYLINDER

##### TECHNICAL SPECIFICATIONS

MODEL	PUMP	TANK	HP	VOLT	AIR DISPLACEMENT (L/MIN)	BAR	RPM	SIZE	KG
BX39/300T3+3	BX39	300	3 + 3	380	630	10	1400	185 X 60 X 112	150
BX49/300T4+4	BX49	300	4 + 4	380	1082	10	1400	185 X 60 X 112	175
BX59/500T5,5+5,5	BX59	500	5,5 + 5,5	380	1212	11	1400	203 X 68 X 131	270
BX60/500T7,5+7,5	BX60	500	7,5 + 7,5	380	1596	11	1400	203 X 68 X 131	290
BX60/900T7,5+7,5	BX60	900	7,5 + 7,5	380	1596	11	1400	212 X 90 X 158	380
BX70/500T10+10	BX70	500	10 + 10	380	2492	11	1320	203 X 68 X 131	341
BX70/900T10+10	BX70	900	10 + 10	380	2492	11	1320	212 X 90 X 158	431

#### CAST IRON CYLINDER

##### TECHNICAL SPECIFICATIONS

MODEL	PUMP	TANK	HP	VOLT	AIR DISPLACEMENT (L/MIN)	BAR	RPM	SIZE	KG
BX39G/300T3+3	BX39G	300	3 + 3	380	630	10	1400	185 X 60 X 112	156
BX49G/300T4+4	BX49G	300	4 + 4	380	1082	10	1400	185 X 60 X 112	183
BX59G/500T5,5+5,5	BX59G	500	5,5 + 5,5	380	1212	11	1400	203 X 68 X 131	280
BX60G/500T7,5+7,5	BX60G	500	7,5 + 7,5	380	1596	11	1400	203 X 68 X 131	300
BX60G/900T7,5+7,5	BX60G	900	7,5 + 7,5	380	1596	11	1400	212 X 90 X 158	390
BX70G/500T10+10	BX70G	500	10 + 10	380	2492	11	1320	203 X 68 X 131	359
BX70G/900T10+10	BX70G	900	10 + 10	380	2492	11	1320	212 X 90 X 158	449
BX80G/900T15+15	BX80G	900	15 + 15	380	3010	11	1320	212 X 90 X 158	475