

6 SILENT BELT DRIVEN

6.3 ON TANK WITH DRYER



TECHNICAL SPECIFICATIONS

MODEL	PUMP	TANK	HP	VOLT	AIR DISPLACEMENT (L/MIN)	BAR	RPM	SIZE	KG
BX59GSIL/500FT 5,5D	BX59G	500	5,5	380	606	11	1400	203 X 66 X 150	300
BX60GSIL/500FT 7,5D	BX60G	500	7,5	380	798	11	1400	203 X 66 X 150	315
BX70GSIL/500FT 10D	BX70G	500	10	380	1246	11	1320	203 X 74 X 157	340
BX80GSIL/500FT 15D	BX80G	500	15	380	1370	11	1320	203 X 74 X 157	350

WITH STAR DELTA STARTER

TECHNICAL SPECIFICATIONS

MODEL	PUMP	TANK	HP	VOLT	AIR DISPLACEMENT (L/MIN)	BAR	RPM	SIZE	KG
BX59GSIL/500FT 5,5SDSD	BX59G	500	5,5	380 Δ	606	11	1400	203 X 66 X 150	304
BX60GSIL/500FT 7,5SDSD	BX60G	500	7,5	380 Δ	798	11	1400	203 X 66 X 150	319
BX70GSIL/500FT 10SDSD	BX70G	500	10	380 Δ	1246	11	1320	203 X 74 X 157	344
BX80GSIL/500FT 15SDSD	BX80G	500	15	380 Δ	1370	11	1320	203 X 74 X 157	354