



- COAXIAL DRIVE screw compressor on tank with dryer*
- Oil separator filter SPIN-ON*
- Oil filter SPIN-ON*
- Oil/air cooling through electrically aired radiator*
- Operating load and load with timed shutdown*
- Delta-star starting*
- Electronic control card*
- Dryer with BY - PASS equipped*
- On demand is available version with "inverter"*

TECHNICAL SPECIFICATIONS

<i>MODEL</i>	<i>HP</i>	<i>BAR</i>	<i>AIR Delivered (Lt/min)</i>	<i>Volt/ph/Hz</i>	<i>db-A</i>	<i>TANK</i>	<i>SIZE</i>	<i>KG</i>
DEB-270-5,5E	5,5	10	550	400/3/50	70	270	55 X 160 X 145	242
DEB-270-7,5E	7,5	10	750	400/3/50	70	270	55 X 160 X 145	244
DEB-270-10E	10	10	1000	400/3/50	70	270	55 X 160 X 145	246
DEB-500-5,5E	5,5	10	550	400/3/50	70	500	60 X 195 X 150	296
DEB-500-7,5E	7,5	10	750	400/3/50	70	500	60 X 195 X 150	298
DEB-500-10E	10	10	1000	400/3/50	70	500	60 X 195 X 150	300