



These air compressors are complete of special tubes of cooling between 1st and 2nd stage. Are also complete of tubes of delivery, non return valve, tele-pressure switch, safety valve and flywheel in cast iron.

The models over 30 bar are assembled with non return valve Hoerbiger type. The air compressors with power from 7.5 HP are complete with star-delta starter in box and solenoid valve.

TECHNICAL SPECIFICATIONS

MODEL	TANK Lt.	HP	Volt/ Phase	Starter	AIR Delivered (L/min)	BAR	RPM	SIZE	KG
BX90/2-20M	2	2	230/1	Direct	90	20	1400	56 X 31 X 55	33
BX200/50-15T	50	3	400/3	Direct	200	15	870	95 X 35 X 71	65
BX220/100-15T	100	4	400/3	Direct	220	15	950	128 X 40 X 84	85
BX360/300-15T	300	5,5	400/3	Direct	360	15	830	155 X 60 X 120	110
BX580/300-15T	300	7,5	400/3	Direct	580	15	820	155 X 60 X 120	180
BX880/500-15T	500	10	400/3	Direct	880	15	920	197 X 60 X 123	310
BX190/120-20T	120	4	400/3	Direct	190	20	850	128 X 40 X 84	85
BX640/250-20T	250	10	400/3	Direct	640	20	970	155 X 60 X 120	290
BX400/250-20T	250	7,5	400/3	Direct	400	20	970	155 X 60 X 120	220
BX130/120-30T	120	4	400/3	Direct	130	30	1050	140 X 60 X 123	220
BX360/300-15SD	300	5,5	400/3	Star / Delta	360	15	830	155 X 60 X 120	110
BX580/300-15SD	300	7,5	400/3	Star / Delta	580	15	820	155 X 60 X 120	180
BX880/500-15SD	500	10	400/3	Star / Delta	880	15	920	197 X 60 X 123	310
BX400/250-20SD	250	7,5	400/3	Star / Delta	400	20	970	155 X 60 X 120	220
BX640/250-20SD	250	10	400/3	Star / Delta	640	20	990	155 X 60 X 120	290
BX800/475-20SD	475	12,5	400/3	Star / Delta	800	20	920	197 X 60 X 123	320
BX180/120-30SD	120	7,5	400/3	Star / Delta	180	30	720	140 X 60 X 123	240
BX400/300-30SD	300	10	400/3	Star / Delta	400	30	800	180 X 75 X 141	423
BX600/300-30SD	300	12,5	400/3	Star / Delta	600	30	760	180 X 75 X 141	450
BX550/300-35SD	300	12,5	400/3	Star / Delta	550	35	850	180 X 75 X 141	430