

## 11.2 ON BASE



*These air compressors on base are machines built for elevated performance.*

*The models with pressure 30 and 35 bar are supplied with heat exchanger and electro-fan between the 1st and 2nd stage, separator and electronic condensate drain, non return valve. Hoberbiger type, suction gauge and delivery gauge.*

### TECHNICAL SPECIFICATIONS

MODEL	HP	Starter	AIR Delivered (L/min)	BAR	RPM	SIZE	KG
BX220-15	4	Direct	220	15	950	73 X 36 X 40	63
BX190-20	4	Direct	190	20	850	73 X 41 X 40	63
BX130-30	4	Direct	130	30	1050	105 X 52 X 76	63
BX360-15	5,5	Direct	360	15	830	75 X 40 X 60	80
BX400-20	7,5	Star / Delta	400	20	970	75 X 40 X 60	82
BX280-30	7,5	Star / Delta	280	30	720	105 X 52 X 76	82
BX580-15	7,5	Star / Delta	580	15	820	96 X 59 X 60	210
BX640-20	10	Star / Delta	640	20	990	96 X 59 X 60	212
BX400-30	10	Star / Delta	400	30	800	130 X 58 X 85	218
BX880-15	10	Star / Delta	880	15	920	100 X 60 X 67	245
BX800-20	12,5	Star / Delta	800	20	920	100 X 60 X 67	245
BX600-30	12,5	Star / Delta	600	30	760	130 X 58 X 85	245
BX550-35	12,5	Star / Delta	550	35	850	130 X 58 X 85	220
BX450-40	12,5	Star / Delta	450	40	860	130 X 58 X 85	240