

11 HIGH PRESSURE AIR COMPRESSORS

11.4 BOOSTER



The series **BOOSTER** allows retrieving compressed air at medium pressure (from 6 to 10 BAR) from a tank or either directly by a compressor and recompress it to a final pressure which reach up to 40 BAR

TECHNICAL SPECIFICATIONS

MODEL	HP	Volt/Phase	AIR Delivered (L/min)	BAR Input	BAR Output	SIZE	KG
BX10/6-30	10	400/3	1500	6	30	170 X 85 X 80	305
BX10/6-35	10	400/3	1300	6	35	170 X 85 X 80	305
BX10/6-40	10	400/3	1200	6	40	170 X 85 X 80	305
BX15/6-30	15	400/3	2100	6	30	170 X 85 X 80	316
BX15/8-30	15	400/3	2700	8	30	170 X 85 X 80	316
BX15/10-30	15	400/3	3000	10	30	170 X 85 X 80	316
BX15/6-35	15	400/3	1850	6	35	170 X 85 X 80	316
BX15/8-35	15	400/3	2500	8	35	170 X 85 X 80	316
BX15/10-35	15	400/3	2800	10	35	170 X 85 X 80	316
BX15/6-40	15	400/3	1800	6	40	170 X 85 X 80	316
BX15/8-40	15	400/3	2350	8	40	170 X 85 X 80	316
BX15/10-40	15	400/3	2700	10	40	170 X 85 X 80	316
BX20/6-30	20	400/3	2150	6	30	170 X 85 X 80	330
BX20/8-30	20	400/3	2900	8	30	170 X 85 X 80	330
BX20/10-30	20	400/3	3400	10	30	170 X 85 X 80	330
BX20/6-35	20	400/3	2150	6	35	170 X 85 X 80	330
BX20/8-35	20	400/3	2900	8	35	170 X 85 X 80	330
BX20/10-35	20	400/3	3500	10	35	170 X 85 X 80	330
BX20/6-40	20	400/3	2000	6	40	170 X 85 X 80	330
BX20/8-40	20	400/3	2800	8	40	170 X 85 X 80	330
BX20/10-40	20	400/3	3400	10	40	170 X 85 X 80	330