

14.5 ACTIVATED CARBON FILTER (BLACK)

Activated carbon filter for the elimination of oil vapours and odour.

When installed, after a 0,01 micron grade filter, it lowers the maximum contents of residual oil 0,003 mg/m³.

Used in the pharmaceutical industry, for dental applications, in photographic workshops, packaging and galvanic treatments.

The item is supplied with aluminum body, filter cartridge, manual drain valve and packaged in single carton box.

The differential gauge is optional.



TECHNICAL SPECIFICATIONS

| Item | N Lt/min | N m ³ /h | Connections | Dimensions mm. | Weight kg. |
|--------|----------|---------------------|-------------|----------------|------------|
| FAC008 | 850 | 51 | 3/8 | 85 X 187 | 0,77 |
| FAC012 | 1200 | 72 | 1/2 | 85 X 187 | 0,77 |
| FAC018 | 1850 | 111 | 3/4 | 85 X 256 | 0,88 |
| FAC030 | 3300 | 198 | 1" | 125 X 263 | 2,2 |
| FAC055 | 5500 | 330 | 1"-1/2 | 125 X 362 | 2,6 |
| FAC080 | 8100 | 486 | 1"-1/2 | 125 X 452 | 2,9 |
| FAC120 | 12500 | 750 | 1"-1/2 | 125 X 643 | 3,7 |
| FAC160 | 16800 | 1008 | 2" | 160 X 695 | 7,4 |
| FAC250 | 26000 | 1560 | 2"-1/2 | 160 X 935 | 10 |
| FAC400 | 42000 | 2520 | 3" | 250 X 1170 | 25 |